



1650 McReynolds Avenue, N.W.
Grand Rapids, Michigan 49504-2043
Phone: (616) 363-4416 Fax: (616) 363-0380
www.bulmanproducts.com

OPERATING INSTRUCTIONS

M800-36 & M800-48 MEASURING DEVICE

FOR USE WITH THE BULMAN

R200 20 ROLL HORIZONTAL RACK

LOADING

1. The Bulman M800 measuring device is shipped assembled and virtually ready to use. Simply lower the M800 down the square tube uprights of a Bulman R200 dispenser and tighten the black toggle knobs to secure. Keep the measuring device as level as possible in order to avoid telescoping during the re-rolling process.

DISPENSING

1. Make sure that the roll of paper to be measured from is below the M800 table surface. If you prefer you may move the roll of paper you want to dispense to the proper location. This may be the easiest method for you to dispense.
2. Only dispense one roll at a time and when finished with that roll, wind it back up. You are now ready for the next roll.

SET UP FOR MEASURING

1. Keep the Trim Master cutter at either end of the Trim Master cutting track.
2. Swing the measuring wheel up and back off the table surface. Pull the desired paper onto the table surface so that the leading edge is in line with the Trim Master cutting track. This will always be your starting point.
3. Center the measuring device and swing back and down onto the paper. Remember to reset the meter.

WINDING THE PAPER

1. Pull enough paper out so it can be wound at least one time over the wind-up tube. With your right hand, turn the crank handle towards you, while your left hand cups the paper around the wind-up tube. While turning the crank handle, apply enough pressure with your left hand in order to tuck the paper onto the wind-up tube. Even if the paper starts to slip, the measuring device will still measure accurately.



1650 McReynolds Avenue, N.W.
Grand Rapids, Michigan 49504-2043
Phone: (616) 363-4416 Fax: (616) 363-0380
www.bulmanproducts.com

2. If the paper begins to telescope, or winds up with uneven tightness, you can straighten the paper. Place your left hand on the center of the paper on the wind-up tube and turn the handle in the reverse direction. Straighten the paper and then continue to wind it onto the roll.

CUTTING & REMOVING THE WOUND ROLL

1. Once the measuring meter has reached the desired length you are now ready to cut and tape the re-rolled amount.
2. The paper must be taut at the cutting end. To begin cutting, place your thumb and forefinger on either side of the cutting track, tightening the paper over the track. While taut, begin sliding the Trim Master cutter to the other end. Once initially cut, the cutter should easily slide through the paper without the paper needing to be held.
3. Loosely tape the end of the paper to the roll allowing the inner rolls to release themselves from the wind-up tube.
4. After taping, push the tube towards the crank handle as far as the spring-loaded end will allow. This should leave sufficient room for the left side of the tube to be removed from its slot.
5. Lift the roll and wind-up tube and stand it on end. Then guide the tube out of the wound roll. Replace the winding tube by fitting the grooves on one end of the tube with the dowel pins. Push towards the crank handle and install the other end.

M800 MANUAL MEASURE-A-ROLL

(TOGGLE CLAMP STYLE)

